



Alpine





Alpine

Alpine is nice and authentic bouclé woven quality which is a perfect fit for our Comfort collection. Softness, volume and elegance are characteristic of this collection.

We added this article following the latest trends and market demand.

Alpine combines polyester and polyacrylic yarns, twisted to make a beautiful upholstery fabric. Bouclé yarns are really fun to spin. Made by first creating loose loops around a core yarn, bouclé yarns look marvellous and are a very popular choice in furniture fabrics. This article can be applied widely: perfect for loose covers and easily upholstered on tight fitted models. It will fit every style; even accessories and clothing look good in bouclé!

But please be aware that the fabric is sensitive to damage from sharp tools, belts, jewelry and pets. Loops or loose threads can appear and can be pushed back in the fabric with a blunt object. Make sure never to pull or cut the thread. Nonetheless, it is just this wonderful texture - formed by the varying size of loops, from large and loose curls to small and tight circlets - that makes a bouclé fabric so attractive.

This flatwoven, yarn dyed quality is washable at 30 degrees machine wash. When washing always wash the cover inside out and put the cover directly back on the furniture, so it can dry evenly.

Textafoam^{originals} Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ Faceside 96%PES 4%PAC
/ Polyester polyacrylic flatweave

Suitable for


Sofa's, beds, chairs with fitted
and loose fitting upholstery



ivory 101




natural 01



steel 149



brown 15



grey 65



darkbrown 18



onyx 169

Alpine - Article passport

Nice and authentic bouclé woven quality with a soft and full grip and a rich appearance.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	polyester polyacrylic flatweave
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery
Composition faceside	96%PES 4%PAC
Statistic Code	54079300
Dyeing method	yarn dyed
Available colours	7

Durability specifications

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				DRY	WET	DGM	DGM+	
Abrasion Resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	75.000		min. 8.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11, 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-B02:2014-11, Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min. 5	B
	middle colours	CTL	grade	5		min. 4	min. 5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
Colour fastness to rubbing	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	Ignatability	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) Regulations: 1988 No. 1324, Schedule 4 part I. Ignition source 0: cigarette	CTL		passed			

Processing specifications

Minimum workable width in centimeters	± 143							
Roll length in meters	± 35							
Material weight in grams per linear meter	± 680							
Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.514	717	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	136,9	176,3	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07, Load 180 N	CTL	mm	2,0	2,0	max. 5	max. 4	A/A
Chemical substances	REACH	Centexbel		passed				

Cleaning specifications

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Dimensional change for washing 30 degrees celsius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,4	-2,0	n/a	n/a	A/A
 <p>We recommend to immediately place the cover back to the piece of furniture slightly damp after washing</p>								



Textaafoam
creativity in fabrics

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl